



3/8" Air Dielectric, Plenum Rated (CATVP), HS Series – 50-ohm



HS2RP-50

Description	Type No.
Cable Ordering Information	
Plenum Cable	
3/8" Fire Retardant Cable	HS2RP-50
Characteristics	
Electrical	
Impedance, ohms	50 ± 1
Maximum Frequency, GHz	13.4
Velocity, percent	83
Peak Power Rating, kW	13.2
dc Resistance, ohms/1000 ft (1000 m)	
Inner	1.41 (4.64)
Outer	1.52 (4.99)
dc Breakdown, volts	2300
Jacket Spark, volts RMS	5000
Capacitance, pF/ft (m)	23.61 (77.47)
Inductance, µH/ft (m)	0.064 (0.208)
Mechanical	
Outer Conductor	Copper
Inner Conductor	Copper-Clad Aluminum
Diameter over Jacket, in (mm)	0.415 (10.5)
Diameter over Copper Outer Conductor, in (mm)	0.375 (9.5)
Minimum Bending Radius, in (mm)	1 (25)
Number of Bends, minimum	20 (50)
Bending Moment, lb-ft (N·m)	1.8 (2.45)
Cable Weight, lb/ft. (kg/m)	0.076 (0.113)
Tensile Strength, lb (kg)	210 (95)
Flat Plate Crush Strength, lb/in (kg/mm)	100 (1.8)

Attenuation and Average Power Ratings

Frequency MHz	Attenuation dB/100 ft	Attenuation dB/100 m	Average Power, kW
0.5	0.083	0.273	13.2
1	0.118	0.386	13.2
1.5	0.144	0.473	12.1
2	0.166	0.546	10.5
10	0.374	1.23	4.67
20	0.530	1.74	3.30
30	0.650	2.13	2.69
50	0.843	2.76	2.07
88	1.12	3.69	1.55
100	1.20	3.94	1.46
108	1.25	4.09	1.40
150	1.48	4.84	1.18
174	1.59	5.23	1.10
200	1.71	5.62	1.02
300	2.11	6.93	0.827
400	2.45	8.05	0.712
450	2.61	8.56	0.670
500	2.76	9.04	0.634
512	2.79	9.16	0.626
600	3.03	9.95	0.576
700	3.29	10.8	0.531
800	3.53	11.6	0.495
824	3.59	11.8	0.487
894	3.75	12.3	0.466
960	3.89	12.8	0.449
1000	3.98	13.0	0.439
1250	4.48	14.7	0.390
1500	4.94	16.2	0.354
1700	5.29	17.4	0.330
1800	5.46	17.9	0.320
2000	5.78	19.0	0.302
2100	5.94	19.5	0.294
2200	6.09	20.0	0.287
2300	6.24	20.5	0.280
3000	7.23	23.7	0.242
3400	7.75	25.4	0.226
4000	8.49	27.8	0.206
5000	9.63	31.6	0.182
6000	10.7	35.1	0.164
8000	12.6	41.4	0.138
10000	14.4	47.2	0.121
12000	16.1	52.7	0.109
13400	17.2	56.3	0.102

Standard Conditions:

For attenuation, VSWR 1.0, ambient temperature 20°C (68°F).

For Average Power, VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F), no solar loading.